






Certified by the German TÜV - SÜD Product Service Institute according to the European Standard in force EN 1176. Structure made of glued laminated pine timber pressure treated with non-toxic salts. Components: No.1 tower with wood posts section 7x7 cm, equipped with a gable roof and coloured bilaminate protective panels HPL 5 mm thick pantographed without sharp edges, equipped with one film coated multi-layer birch wood platform (CARPLY) Dim. 70x70x250Ht. cm; No.1 tower with wood posts section 7x7 cm, equipped with coloured bilaminate protective panels HPL 5 mm thick pantographed without sharp edges, equipped with one film coated multi-layer birch wood platform (CARPLY) Dim. 70x70x153Ht. cm; No.1 access stair in painted electro galvanized tubular steel Ø 30 mm in diameter; high pressure laminate side panels (HPL) and stair treads in polyethylene PEHD 15 mm thick pantographed without sharp edges; No.1 tunnel that connects the two towers and 1 slide both in fiberglass realized in high-density multiple layers of resin. Assembly system with 8.8 galvanized steel bolts and self- locking nuts. Coloured nylon cap nuts as required by law. Polyethylene pole caps. Baked finishing at 180°C.

 cm 250x232x230h INGOMBRO MAX	 80 ALTEZZA CADUTA	 CERTIFICATO EN 1176
 3-8 ETÀ D'USO	 5 h TEMPO DI ASSEMBLAGGIO	
 5 NUMERO UTILIZZATORI	 cm 575x550 SPAZIO MINIMO	
 m ² 28 AREA IMPATTO		

Planimetria / Planimetry

