



Certified by the German TÜV – SÜD Product Service Institute according to the European Standard in force EN 1176. Structure made of posts in aluminium alloy EN AW 6060 section 70x70 mm and stratified bilaminate HPL panels pantographed without sharp edges. Components: No.1 access ladder with lateral supports in stratified bilaminate HPL 15 mm as handrails and rungs in galvanized tubular steel Ø 30 mm with non-slip PVC surface. No.1 slide 100 cm Height in in rotomolded coloured high-density polyethylene connected to the structure through stratified bilaminate HPL panels 15 mm thick. No.1 decorative roof with three elliptical elements made of stratified bilaminate HPL panels pantographed without sharp edges. Assembly system with 8.8 galvanized steel bolts and self-locking nuts. Colored nylon cap nuts as required by law. Polyethylene post caps. Polyester powder coating at 180°C. with very high resistance to atmospheric agents and UV rays. Hot-dip galvanized steel brackets for ground anchoring system.



cm 116x282x350h  
**INGOMBRO MAX**



92  
**ALTEZZA CADUTA**



**CERTIFICATO EN 1176**



2-8  
**ETÀ D'USO**



2 h  
**TEMPO DI ASSEMBLAGGIO**



2  
**NUMERO UTILIZZATORI**



cm 500x375h  
**SPAZIO MINIMO**



m<sup>2</sup> 19,00  
**AREA IMPATTO**

Planimetria / Planimetry

