



In accordance with the European Standard EN 16630. Structure composed by structural posts sized 200x120mm, made of 3mm S235Jgrade steel; Anchoring posts sized 300x300mm, made of 10mm S235Jgrade steel, with pilot holes for anchoring to the ground or to anchors; Casings and surface details made of laser-cut, 3–10mm S235J-grade steel; Handles sized 30mm, made of 2mm S235J-grade steel; Frame made of 3mm S235J-grade steel tubing sized 50x30mm.; Recycled SBR plastic footboards; Steel bearings sized ? 37mm, in watertight casings; Flywheel casing boxed in 14mm plain green HDPE, with UV-proof pigmentation and rounded edges; Flywheel casing sealed with a 1mm plate of SAE 304 stainless steel; Ball spline assembly for disc rotation, with steel bearings sized 48mm, in watertight casings. Assembly system with 8.8 galvanized steel bolts and self- locking nuts. Nut caps made of engineering plastic as required by law. Finishing of fitness equipment: sandblasting, protective primer, bed-dip coating in grey and black RILSAN. Finishing of structural posts: sandblasting, cold galvanizing, RAL 9005 powder coating. **Available in the following versions:**

- Type **A** (TO PLOUGH IN) with hot-dip galvanized steel anchors;
- Type **B** (TO FIX ON THE FLOOR), with hot-dip galvanized steel brackets for fixing using "FISHER" type anchors or similar, **NOT SUPPLIED.**


Supplied in an **assembly-kit**.

 cm 2080x580x1600h
INGOMBRO MAX

 100
ALTEZZA CADUTA

 1 h
TEMPO DI ASSEMBLAGGIO

 1
NUMERO UTILIZZATORI

 cm 510x360
SPAZIO MINIMO

 m² 0,00
AREA IMPATTO

Planimetria / Planimetry

