



**In accordance with the European Standard EN 16630. CROSS TRAINER** Structure composed by structural posts sized 200x120mm, made of 3mm S235J-grade steel. Anchoring posts sized 300x300mm, made of 10mm S235J-grade steel, with pilot holes for anchoring to the ground or to anchors; Casings and surface details made of laser-cut, 3–10mm S235J-grade steel; Handles sized 30mm, made of 2mm S235J-grade steel; Frame made of 3mm S235J-grade steel tubing sized 50x30mm; Recycled SBR plastic footboards; Steel bearings sized 37mm, in watertight casings; Flywheel casing boxed in 14mm plain green HDPE, with UV-proof pigmentation and rounded edges; Flywheel casing sealed with a 1mm plate of SAE 304 stainless steel; Ball spline assembly for disc rotation, with steel bearings sized 48mm, in watertight casings. **EXERCISE BIKE** Structure composed by structural posts sized 200x120mm, made of 3mm S235J-grade steel; Structural posts sized 200x120mm, made of 3mm S235J-grade steel; Anchoring posts sized 300x300mm, made of 10mm S235J-grade steel, with pilot holes for anchoring to the ground or to anchors; Casings and surface details made of laser-cut, 3–10mm S235J-grade steel; Seating made of 19mm two-colour HDPE, with UV-proof pigmentation, rounded edges, and non-slip textured surface; Handles sized 30mm, made of 2mm S235J-grade steel; Vibration dampers and limit stop sized 50mm and made of rubber, with M10 threaded stud; Flywheel casing boxed in 14mm plain green HDPE, with UV-proof pigmentation and rounded edges; Flywheel casing sealed with a 1mm plate of SAE 304 stainless steel; Ball spline assembly for disc rotation, with steel bearings sized 48mm, in watertight casings; Adjustable seating, four positions selected using the knob on the side of the seat. Sliding guides made of aluminium sized 60x40mm. Assembly system with 8.8 galvanized steel bolts and self-locking nuts. Nut caps made of engineering plastic as required by law. Finishing of fitness equipment: sandblasting, protective primer, bed-dip coating in grey and black RILSAN. Finishing of structural posts: sandblasting, cold galvanizing, RAL 9005 powder coating. **Available in the following versions:**

- Type A (TO PLOUGH IN) with hot-dip galvanized steel anchors;
- Type B (TO FIX ON THE FLOOR), with hot-dip galvanized steel brackets for fixing using "FISHER" type anchors or similar, **NOT SUPPLIED**.

Supplied in an **assembly-kit**.

 cm 3400x560x1600h  
**INGOMBRO MAX**

 < 1m  
**ALTEZZA CADUTA**

 1 h  
**TEMPO DI ASSEMBLAGGIO**

 2  
**NUMERO UTILIZZATORI**

 cm 640x360  
**SPAZIO MINIMO**

 m<sup>2</sup> 0,00  
**AREA IMPATTO**

**Planimetria / Planimetry**

