



Certified by the German TÜV - SÜD Product Service Institute according to the European Standard in force EN 1176. Structure made of glued laminated pine timber pressure treated with non-toxic salts. Components: No.1 tower with wood posts section 7x7 cm, equipped with one gable roof and coloured high pressure laminate protection panels (HPL) 5 mm thick pantographed without sharp edges, equipped with one film coated multi-layer birch wood platform (CARPLY) Dim. 70x70x250Ht. cm.; No.1 tower with wood posts section 7x7 cm, equipped with coloured high pressure laminate protection panels (HPL) 5 mm thick pantographed without sharp edges, equipped with one film coated multi-layer birch wood platform (CARPLY) Dim. 70x70x153Ht. cm; No.1 access stair in painted electro galvanized tubular steel Ø 30 mm in diameter; high pressure laminate side panels (HPL) and stair treads in polyethylene PEHD 15 mm thick pantographed without sharp edges; No.1 slide in fiberglass realized in high-density multiple layers of resin. Assembly system with 8.8 galvanized steel bolts and self- locking nuts. Coloured nylon cap nuts as required by law. Polyethylene pole caps. Baked finishing at 180°C.



cm 200x250x250h
INGOMBRO MAX



cm 98
ALTEZZA CADUTA



CERTIFICATO EN 1176



3-8 years
ETÀ D'USO



4 h
TEMPO DI ASSEMBLAGGIO



4
NUMERO UTILIZZATORI



cm 600x500
SPAZIO MINIMO



m² 27
AREA IMPATTO

Planimetria / Planimetry

