



Certified by the German TÜV - SÜD Product Service Institute according to the European Standard in force EN 1176. Structure made of glued laminated pine timber pressure treated with non-toxic salts. Components: No.1 tower with wood posts section 7x7 cm and coloured high pressure laminate protection panels (HPL) 5 mm thick pantographed without sharp edges, equipped with one film coated multi-layer birch wood platform (CARPLY) Dim. 70x70x153ht. cm. No.1 access stair in painted electro galvanized tubular steel Ø 30 mm in diameter, high pressure laminate side panels (HPL) and stair treads in polyethylene PEHD 15 mm thick pantographed without sharp edges; No.1 slide in fiberglass realized in high-density multiple layers of resin. Assembly system with 8.8 galvanized steel bolts and self- locking nuts. Coloured nylon cap nuts as required by law. Polyethylene pole caps. Baked finishing at 180°C.

 cm 130x230x153h
INGOMBRO MAX


 80
ALTEZZA CADUTA

 **CERTIFICATO EN 1176**

 3-8
ETÀ D'USO

 1,5 h
TEMPO DI ASSEMBLAGGIO

 3
NUMERO UTILIZZATORI

 cm 575x425h
SPAZIO MINIMO

 m² 23
AREA IMPATTO

Planimetria / Planimetry

