



Playground Cableway Illinois. Certificate in accordance with European Standards EN 1176 by the German TÜV - SÜD. Made of wood laminated pine timber autoclave with non-toxic salts. Parts list: N°2 vertical poles section 12x12 cm to be anchored to the ground at different heights on the back and connected to two inclined rods made of tubular galvanized steel Ø 60 mm thick in the oven to 180°. N°2 forms of support and reinforcement of the mast section made of wooden poles 9x9 cm, mahogany plywood panels okoumé grooved phenolic-glued and free of sharp edges and spurs of tubular galvanized steel and painted in phono to 180°C. The starting module is provided in a platform, phenolic glued birch plywood finished with colored films on both sides. N°1 on cable sliding system in galvanized steel more strands of elastic devices full stop at the ends. N°1 seat plane circular rubber bumper with internal steel plate bent and suspended from a chain-mesh welded and hot-dip galvanized. All the wooden parts are treated with high-colored stain penetration, non-toxic, wax-based water-soluble. Assembled by 8.8 galvanized steel bolts and nuts. Elements covernut under colored nylon. Attacks galvanized metal for anchoring to the ground.

cm 1330x110x324h  
**INGOMBRO MAX**

cm 100  
**ALTEZZA CADUTA**



**CERTIFICATO EN 1176**

3-8 years  
**ETÀ D'USO**

2 h  
**TEMPO DI ASSEMBLAGGIO**

1  
**NUMERO UTILIZZATORI**

cm 1375x400  
**SPAZIO MINIMO**

m<sup>2</sup> 53,00  
**AREA IMPATTO**

Planimetria / Planimetry

