
Hydra Seesaw Springer

Codice: **1086**



Certified by the German TÜV – SÜD Product Service Institute according to the European Standard in force EN 1176. Structure made of painted electro galvanized steel, baked finishing at 180°C. Triangular chassis in tubular electro-galvanized steel section Ø 40 mm and a shaped sheet-metal in electro-galvanized steel 4 mm thick, equipped with decorative coloured panels in polyethylene PEHD 1 cm thick, pantographed without sharp edges. Each end of the seesaw springer has a handhold/footrest device in tubular electro galvanized steel section Ø 30 mm and coloured polyethylene seat (PEHD) 15 mm thick, pantographed without sharp edges. The structure is clamped on 3 painted steel springs, certified with anti-pinch system. Assembly system with 8.8 galvanized steel bolts and self-locking nuts. Coloured nylon cap nuts as required by law. Hot-dip galvanized steel brackets for ground anchoring system.

cm 189x167x67h
INGOMBRO MAX

cm 48
ALTEZZA CADUTA

CERTIFICATO EN 1176

2-8 years
ETÀ D'USO

1,5 h
TEMPO DI ASSEMBLAGGIO

3
NUMERO UTILIZZATORI

cm 425x400
SPAZIO MINIMO

m² 17
AREA IMPATTO

Planimetria / Planimetry

